Listing and Amendments to the Claims 10/540244 Contract of PCT/PTO 22 JUN 2005

This listing of claims will replace the claims that were published in the PCT Application:

- 1. (original) A method of correcting a color characteristic of an image displayed in response to a video signal comprising the steps of:
- A) processing the video signal for predicting a variation in a physical characteristic of a display device displaying the image;
- B) processing the video signal for determining a change in the color characteristic occurring in response to the variation in the physical characteristic; and
- C) modifying the video signal for compensating for the change in the color characteristic.
- 2. (original) The method of claim 1 wherein the display device comprises a color picture tube and wherein step A comprises the steps of:

processing the video signal for predicting a temperature distribution of a mask of the color picture tube; and

predicting a change in a location of an aperture of the mask relative to an initial location occurring in response to the temperature distribution.

3. (original) The method of claim 1 wherein the display device comprises a color picture tube and wherein step B comprises the steps of:

determining a change in a register characteristic of an electron beam occurring in response to the variation in the physical characteristic; and

determining a change in the color characteristic occurring in response to the change in the register characteristic.

4. (original) The method of claim 2 wherein step B comprises the steps of:

determining a change in a register characteristic of an electron beam occurring in response to the change in the location of the aperture in the mask; and

determining a change in the color characteristic occurring in response to the change in the register characteristic.

5. (currently amended) The method of claim 2 or claim 4 wherein the step of determining the temperature distribution comprises the steps of

determining the temperature distribution relative to a reference temperature distribution; and

integrating an effect of a current density distribution of a beam current of the color picture tube on the mask over time.

- 6. (currently amended) The method of claim 3 or 4 wherein the step of determining a change in the register characteristic comprises the step of processing the video signal for predicting a space charge repulsion characteristic associated with a plurality of electron beams projected through the mask.
- 7. (currently amended) The method of claim 1, 5, or 6 wherein the step of modifying the video signal comprises the steps of:

determining a change in a beam current of the color picture tube necessary to compensate for the change in the color characteristic; and

modifying the video signal for producing the beam current change.

8. (original) A method of correcting a color characteristic of an image displayed in response to a video signal comprising the steps of:

processing the video signal for determining a temperature variation of a mask of a color picture tube;

determining in response to the temperature variation a change in a location of an aperture of the mask relative to an initial location;

determining in response to the change in location of the aperture a change in a register characteristic of an electron beam projected through the aperture in the mask;

determining a change in the color characteristic occurring in response to the change in the register characteristic; and

modifying the video signal for correcting for the change in the color characteristic.

9. (original) The method of claim 8 wherein the step of determining the change in the register characteristic comprises the step of:

processing the video signal for predicting a space charge repulsion characteristic associated with a plurality of electron beams projected through the mask.

10. (currently amended) The method of claim 8 or 9 wherein the step of modifying the video signal comprises the steps of:

determining a change in a beam current of the color picture tube necessary to compensate for the change in the color characteristic; and

modifying the video signal for producing the beam current change.

11. (original) Apparatus for correcting a color characteristic of an image displayed in response to a video signal comprising:

means for processing a video signal for predicting a variation in a physical characteristic of a display device displaying an image in response to the video signal, and for processing the video signal for determining a change in a color characteristic of the image occurring in response to the variation in the physical characteristic; and

means for modifying the video signal for compensating for the change in the color characteristic.

Amendments to the Abstract

Please add the following Abstract to this application.

-- A system for correcting a color characteristic of an image displayed in response to a video signal involves processing the video signal for predicting a variation in a physical characteristic of a display device displaying the image, processing the video signal for determining a change in the color characteristic occurring in response to the variation in the physical characteristic, and modifying the video signal for compensating for the change in the color characteristic. --